

# DirectTex<sup>®</sup> Softimage Contrast<sup>®</sup>

Field of application

## Blockout

### Specifications



599150 151



100 % polyester  
knit fabrics  
PVC-free, recyclable



ca. 160/ 252/ 260/ 320/ 420/ 505 cm  
ca. 63/ 99/ 102/ 126/ 165/ 199 inch  
other widths available on request



B-s1, d0 DIN EN 13501-1  
Class A ASTM E84-16  
NFPA 701



ca. 220 g/m<sup>2</sup>  
ca. 6.5 oz/yd<sup>2</sup>



ca. 0.37mm  
ca. 370 μm



rolls  
50/ 100 m  
55/ 109 yd



blank: 7  
DIN EN ISO 105-B02



blank: 88.76  
DIN 5033-1



length: 0.9 %  
cross: 0.7 %  
DIN EN 14704-1



cold, ultrasonic cut



gain factor  
blank: 0,93  
DIN 19045-4



length: 448.7 N  
cross: 683.6 N  
DIN EN ISO 13934-1



length: 31.4 %  
cross: 53.3 %  
DIN EN ISO 13934-1



total footprint: 1,399 kg CO<sub>2</sub> eq./m<sup>2</sup>  
determination accuracy: 84%

### Printing methods

print	UV	Latex	Dyesub	UVgel
Inside	•	•	•	•
Outside				

### Article shrinkage

(33 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	0,5 %	1,2 %	185
190°C	/ %	/ %	
200°C	/ %	/ %	
210°C	/ %	/ %	

### Certifications



## DirectTex® Softimage Contrast®

Field of application

### Blockout



Ref.-Nr.: 599150 151 | Preview print sample