














DESCOR®

Diffusor

Fields of application

.01 .02 .04 .05 .06 .07

Specifications

-  **REF.** 599099 141
-  100 % polyester knit fabrics
PVC-free, recyclable
-  ca. 160/ 252/ 320/ 505 cm
ca. 63/ 99/ 126/ 199 inch
other widths available on request
-  B-s1, d0 DIN EN 13501-1
-  ca. 90 g/m²
ca. 2.65 oz/yd²
-  ca. 0.28 mm
ca. 280 µm
-  rolls
100 m
109 yd
-  **Light**
blank: 55.8 %
DIN EN 410
-  length: 395.8 N (15.4 N)
cross: 425.2 N (15.3 N)
DIN EN ISO 13934-1 (13934-2)
-  length: 23.5 %
cross: 64.2 %
DIN EN ISO 13934-1
-  length: 0.7 %
cross: 12.4 %
DIN EN 14704-1
-  **Specs** UV stable
-  cold, heat, ultrasonic cut

Printing methods

print	UV	Latex	Dyesub
Inside	•		•
Outside			

Article shrinkage (50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	0,4 %	1,2 %	•
190°C	0,5 %	1,2 %	
200°C	0,6 %	1,2 %	
210°C	0,7 %	1,5 %	

Certifications





DESCOR® Diffusor

Fields of application

.01 .02 .04 .05 .06 .07



Ref.-Nr.: 599099 141 | Preview print sample



PONGS GROUP GMBH & CO. KG

Bahnhofstraße 21
07919 Pausa-Mühltrorf
Germany

Phone +49 36645 350-0
salestt@pongs.de
www.pongs.com

We reserve the right for technical modifications.
The above mentioned details are non-binding.
A tolerance of $\pm 5\%$ is valid. Effective: 2022/02